## **Vickers**®


## **Directional Controls**



# Wet Armature Solenoid Operated Directional Valves

F6-DG4S4-01\*(\*)C-W3-\*-50







#### NOTE

Part numbers prefixed with a symbol are available only as service kits.

#### NOTE

★ Assemble washer with break edge toward outside of valve.





☐ Included in Fastener Kit 942465

▲ Included in F3 Seal Kit 920109

◆ Included in 941493 AC Core Tube Kit


◆ Included in 941416 DC Core Tube kit

■ Included in Coil Kit			
● Coil S/A	Coil Kit	Model	Coil Code
400823	942466	110/50, 115/60, 120/60	В
400824	942467	220/50, 230/60	D
400825	942468	440/50, 460/60	М
435755	941017	127/50	EG

★ Lot Kits  (25 pcs. only)			
Part #	Kit#		
174638	944054		
286122	944042		
36212	944053		
407533	944040		
416834	944027		
64765	944042		
400809	926310		

### **Model Code**

**L** - Light (Omit for no lights)




1 Seals
F6 - High water base fluids
W3 - Serviceable core tube S/A

2 Model Series
5 Spool Type
B Coil Identification Letter

DG4S4 - Directional valve, manifold or subplate mounted, solenoid operated, sliding spool, 4-way flow direction

B Position
A - Offset

#### For Models with Solenoid Indicator Lights



#### **NOTE**

Refer to parts drawing I-3487-S for models with plug-in feature.

For satisfactory service life of these components in industrial applications, use full flow filtration to provide fluid which meets ISO cleanliness code 18/15 or cleaner. Selections from Eaton OFP, OFR, and OFRS series are recommended.